

1

déberenn

fabrics

xtreme • era • sabine • app

xtreme

group B



era

group B



sabine

group B



app

group B



xtreme

Product information

Xtreme is a modern crepe weave fabric made from 100% post-consumer recycled polyester, diverting waste from landfill and saving virgin raw materials. Its stretch properties, coupled with high flame retardancy, durability and non-pilling properties make Xtreme an ever popular fabric for task seating.

Technical information

Industry Application
Workplace, Education, Hospitality & Leisure
When TriOnyx treated: Healthcare
Composition
100% Post-consumer recycled polyester
Environment
Certified to the EU Ecolabel
Certified to OEKO-TEX® Standard 100
Certified to Indoor Advantage™ Gold
Made from 100% recycled polyester
Non metallic dyestuffs
Width
140 cm minimum
Weight
310 g/m ² ±5% (435 g/lin.m ±5%)
Abrasion Resistance
Heavy duty / 10 year guarantee
Independently certified to ≥100,000 Martindale cycles
Flammability
EN 1021 - 1 [cigarette]
EN 1021 - 2 [match]
BS 7176 Low Hazard
BS 5852 Ignition Source 5
BS 7176 Medium Hazard
DIN 4102 B1
NF D 60-013
ÖNORM B 3825 & A 3800-1
[over 58 kg/m3 CMHR foam]
UNI 9175 Classe 1 IM
BS 476 Part 7 Class 1 [Adhered]
Note: Flammability performance is dependent on components used. Our certificates show what substrates have been used in our tests. For composite tests customers must ensure their complete furniture meets the necessary standards.
Light Fastness
6 [ISO 105 - B02]
Fastness to Rubbing
Wet: 4, Dry: 4 [ISO 105 - X12]
Cleaning
Washable to 60°C. Vacuum regularly. Wipe clean with a damp cloth or shampoo using proprietary upholstery shampoo.

era

Product information

Era is a subtle, two tone polyester fabric containing stretch in both directions for ease of upholstery. The baby herringbone weave offers an understated contemporary texture while its colouring technique provides close up intrigue. The palette incorporates playful brights and sophisticated muted tones.

Technical information

Industry Application
Workplace, Education
Composition
100% Polyester
Environment
Certified to OEKO-TEX® Standard 100
Certified to Indoor Advantage™ Gold
Non metallic dyestuffs
Width
140 cm minimum
Weight
320 g/m ² ±5% (448 g/lin.m ±5%)
Abrasion Resistance
Heavy duty / 10 year guarantee
Independently certified to ≥100,000 Martindale cycles
Flammability
EN 1021 - 1 [cigarette]
EN 1021 - 2 [match]
BS 7176 Low Hazard
EN 13501-1 Adhered Class B, s1, d0 EN 13501-1 Un-adhered Class C, s1, d0
Note: Flammability performance is dependent on components used. Our certificates show what substrates have been used in our tests. For composite tests customers must ensure their complete furniture meets the necessary standards.
Light Fastness
5 [ISO 105 - B02]
Fastness to Rubbing
Wet: 4, Dry: 4 [ISO 105 - X12]
Cleaning
Washable to 60°C. Vacuum regularly. Wipe clean with a damp cloth or shampoo using proprietary upholstery shampoo.

sabine

Product information

Sabine evokes the revival of nature showing its new forms and colours. It offers a combination of enduring aesthetic appeal and high performance durability. The palette incorporates playful brights and sophisticated muted tones.

Technical information

Industry Application
Workplace, Education
Composition
100% Polyester
Width
137 cm minimum
Weight
380 g/m ²
Abrasion Resistance*
40,000 Martindale Cycles
Tear Strength
Weft:154 N -Warp:190N [ISO13937-2]
Fastness to Rubbing
Wet: 5, Dry: 5 [ISO 105 - X12]
Cleaning
Washable to 60°C. Vacuum regularly.
Wipe clean with a damp cloth or shampoo using proprietary upholstery shampoo.
Resistance to seam slippage
Weft:0-1mm - Warp:1-2mm [ISO 13906-2]
Pilling
4 [ISO 12945-2]

app

Product information

APP is a deluxe velvet offering a particular texture and appearance due to its directional pile. Available in a sophisticated color palette, it features soft calming tones and bold statement colors. App has a closely cut pile and is beautifully smooth. Thanks to the satiny sheen of its pile, APP exhibits color in liquid nuance. When upholstered, it almost looks as if has been painted on: the textile seems to recede into the background, creating a rich interplay of color.

Technical information

Roll Length
~ 47 m
Width
140 cm + - 2 cm
Weight m DIN EN 12127
430 g + - 5 %
Composition Surface EU 1007/2011
100% polyester
Composition Base EU 1007/2011
100% polyester
Abrasion Test ENISO 12947-1,2
>25000 cycles
Pilling test EN ISO 12945-2[2.000T]
4
Fastness to Rubbing EN ISO 105-X12 Dry
4
Fastness to Rubbing EN ISO 105-X12 Wet
3
Water Repellent Finishing