

REVO Collection
design by Simone Viola

T O O U



Chair



Stool




Chair with castor base




Stool with castor base


eco plastic, UV resistant



eco white



eco light gray



eco anthracite



eco mustard



eco red terracotta


MEDLEY by **Gabriel**



Upholstery



dark gray





light gray



red terracotta



mustard

Material	polyester	100%
Weight	510 g/lm - (16.45 oz/lin.yd)	
Width	140 cm - (55")	
Abrasion resistance	rubs - EN ISO 12947 - 2 (Martindale)	75,000
Pilling	scale 1-5, max 5 - EN ISO 12945-2	4
Color fastness to light	scale 1-8, max 8 - EN ISO 105 B02	5-7
Color fastness to rubbing	scale 1-5, max 5 - EN ISO 105x12 (wet/dry)	4-5/4-5
Maintenance	dry cleaning  Shrinkage: max. 1%  Shrinkage: max. 3%	
Flammability	EN 1021 1&2 . BS 5852 0&1 . Calif. Tech. Bull. 117 - E . UNI 9175 Class 1 M CA TB 117-2013 - Önorm B 3825-B2 3800 Q1. Will also pass other flammability standards. Flame retardant performance is dependent upon the foam used.	
US ACT	AATCC 16 Light fastness	pass
	AATCC 8 or 116 wet/dry crocking	pass
	California Bulletin CAL 117-E Class 1	pass
	CA TB 117-2013	pass
	ASTM D4157-07 Wyz Abrasion (Heavy Duty Upholstery)	pass
	ASTM D3511 Pilling	pass
Design/Colors	Mette Krebs Petersen	
Subject to changes and color differences		